LOG-PERIODIC BROADBAND 6 EL FM ANTENNA


Log periodic Antenna with 6 elements realized in aluminium that can be used both in FM transmission and reception.

It has a 8 dBi gain and for all 88 -108 Mhz. Band range, it keeps a constant of more than 25 dB in Front to Back ratio.



Tipo		Antenna Log-periodica
Туре		Log-periodic antenna
Polarizzazione		Orizz. / Vert.
Polarization		Horiz./ Vert.
Frequenza		88 – 108 MHz
Frequency		
Impedenza Impedance		50 Ohm
ROS / VSWR		1.15
F/B Ratio		- 25 dB
HPBW		E: 50° H: 103°
Guadagno Gain		8 dBi in tutta la banda 8 dBi all band
Connector		Nf EIA 7/8 Opz.7/16"
Massima potenza Max power		1 kW connettore 7/8 1 kW with 7/8 connector
Materiale Material		Alluminio Aluminium
Dimensioni Dimensions	Α	1.9 mt
	В	1.9 mt
	С	0.2 mt
Peso Weight		8 Kg
Resistenza al vento Wind endurance		120 Km/h
Montaggio Mounting		Montaggio (orizzontale o verticale) singolo o in sistema di antenne con cavallotti per palo Ø114 Single or in antenna system, horizontal or vertical mounting with

RADIATION PATTERNS



GAIN / ROS

