

H.264 CCD IP CAMERA



| | |
|---------------------|--|
| Image Sensor: | Color 1/3 Sony CCD |
| Resolution: | 480 TV Lines |
| Pixels: | NTSC:811(H)x508(V) PAL:795(H)x596(V) |
| TV System: | PAL/NTSC |
| Sync System: | Internal Synchronization |
| Min. Illumination: | 0.2lux/F1.2 |
| S/N Ratio: | More than 48dB(AGC off) |
| Ray Features: | 0.45 |
| Electronic Shutter: | NTSC=1/60-1/100,000 seconds PAL=1/50-1/100,000 seconds |
| Power Supply: | DC12V / 1000mA |
| Operation temp: | -10 to 50 centigrade degree |
| Storage temp: | -20 to 60 centigrade degree |

Features:

- ✓ H.264 compression, best for Internet video Streaming.
- ✓ No Static IP address required, No DDNS service needed.
- ✓ D1 Resolution.
- ✓ Support Win CE based PDA and Mobile Phone local and remote viewing.
- ✓ Support SD/SDHC card recording, NAS recording, NVR recording, and remote view and recording.
- ✓ Multi-streaming capability.
- ✓ Support UPNP protocol.
- ✓ Support DHCP, Static IP, PPPOE internet enviroments.
- ✓ NVR support 128 cameras D1 video recording in LAN. Can manage numerous IP cameras depending on the NVR PC's ability.
- ✓ 3 Level (High, Middle, Low) user priority management.
- ✓ Two-way audio function: audio in and audio out for speaker with amplifier.
- ✓ With BNC connector for composite video output as normal camera.